

TRANSTEC Taper Bushes - Metric Bores & Keyway to DIN 6885 / ISO R773

Bore	Keyway Width	Keyway Depth	Shallow Keyway Depth	Standard Bore Sizes															
				mm	mm	mm	mm	1008	1108	1210	1610	1615	2012	2517	3020	3030	3525	3535	4040
9	3	1.4	-	•	•														
10	3	1.4	-	•	•														
11	4	1.8	-	•	•	•													
12	4	1.8	-	•	•	•													
14	5	2.3	-	•	•	•	•	•	•										
15	5	2.3	-	•	•	•	•	•	•										
16	5	2.3	-	•	•	•	•	•	•	•									
18	6	2.8	-	•	•	•	•	•	•	•	•								
19	6	2.8	-	•	•	•	•	•	•	•	•								
20	6	2.8	-	•	•	•	•	•	•	•	•								
22	6	2.8	-	•	•	•	•	•	•	•	•								
24	8	3.3	1.3	◇	•	•	•	•	•	•	•								
25	8	3.3	1.3	◇	•	•	•	•	•	•	•	•							
28	8	3.3	1.3		◇	•	•	•	•	•	•	•							
30	8	3.3	-			•	•	•	•	•	•	•							
32	10	3.3	-			•	•	•	•	•	•	•							
35	10	3.3	-				•	•	•	•	•	•	•						
38	10	3.3	-				•	•	•	•	•	•	•	•					
40	12	3.3	1.3				•	◇	•	•	•	•	•	•					
42	12	3.3	1.3				•	◇	•	•	•	•	•	•	•				
45	14	3.8	-						•	•	•	•	•	•	•				
48	14	3.8	-						•	•	•	•	•	•	•				
50	14	3.8	-						•	•	•	•	•	•	•				
55	16	4.3	-							•	•	•	•	•	•				
60	18	4.4	-							•	•	•	•	•	•				
65	18	4.4	-								•	•	•	•	•				
70	20	4.9	-									•	•	•	•				•
75	20	4.9	-										•	•	•				•
80	22	5.4	-											•	•				•
85	22	5.4	-												•				•
90	25	5.4	-													•			•
95	25	5.4	-																•
100	28	6.4	-																•
105	28	6.4	-																•
110	28	6.4	-																•
115	32	7.4	-																•
120	32	7.4	-																•
125	32	7.4	-																•

◇ Bushing comes with shallow keyway

TRANSTEC Taper Bushes with Pilot Bores are supplied without slitting to facilitate machining of bore & keyway. Bushes must be slit after final machining for correct installation & operation

	1008	1108	1210	1610	1615	2012	2517	3020	3030	3525	3535	4040	5050
L	22	22	25	25	38	32	45	51	76	63,5	89	102	127
D	35	38	47.5	57	57	70	85.5	108	108	127	127	146	177.5

